

static control made Easy!

Product Specifications

Static Elimination Power Units





*Type indication power supply type A **Options:** S= standard version *E*= *different cable lengths and / or mains* Ayx7z *M*= power supply option for the purposes of systems Type A G= gun Cobra Voltage Voltage secondary: primary: $3 = 3,3 \, kV$ 1= 115V A=50 Hz2 = 230V $5 = 5.0 \, kV$ 3 = 400V $C = 50/60 \, Hz \, 7 = 7.0 \, kV$



A Unit

Active ionisation equipment operates on high voltage. The power units trasform the mains voltage to the high voltage required by the ioniser. There are different typer of power units available. Power units are easily connected and operated and don't need any maintenance.

The standard model has a modern styling featuring easy-acces control and connection. It is equipped with an on/off switch with an indicator lamp as well as a high-voltage indicator lamp. This lamp will extinguish if the system is malfunctioning. 4 ionisers can be connected as a maximum. Variations of the Power Unit:

Ayx4z*

O Ayx5z*

Ayx7z*

• A2A3S; For ionising air nozzle type BW.

• A2A4S; For anti-static bars operating on 4 kV.

A2A5G; For ionising air gun type Cobra.
A2A5S: For anti-static bar type MaxION.

• A2A7S: For anti-static bars operating on 7 kV.

Technical specifications


Housing material	Aluminum and steel, powdercoating
Weight	2,8 kg
Connections	4
On/off switch	Yes with light
High voltage indication	neon lamp
Cable	1,8 m
Ambient temperature	0- 50 °C
Use circumstances	industrial
Protection classification	IP - 54
U primairy	115 V or 230 V or 400 V*
Frequency	50 or 60 Hz or 50/60 Hz*
Power consumption	50 Watt
U secundairy	3,3 - 7 kV AC*
I secundairy	2,5 mA max.
Options	HR, D
Approval	UL*
*Contact Simco-lon for other vo	Itages, frequencies and approvals.

Simco-Ion Netherlands

Postbus 71 Lochem, The Netherlands NL-7240 AB

Tel: +31 (0)573 288333 Fax: +31 (0)573 288380

general@simco-ion.nl www.simco-ion.nl



Technical drawing A Unit

Load (pf per metre)			
75			
75			
65			
75			
100			
450 (incl. 3 metres shielded cable)			
225 (incl. 6 metres cable)			
425 (incl. 12 metres cable)			
75			
65			
125			